



Rev 1  
11/24



# ECOTEK FINISH BIO

Ready-to-use emulsion release agent for high fair-faced finishes



## THE DESCRIPTION

The ECOTEK FINISH BIO release agent is formulated with special synthetic oils of biodegradable additives of vegetable origin, free from toxic substances or harmful to operators and the environment.

ECOTEK FINISH BIO guarantees an excellent finish of fair-faced concrete products, reducing, with very modest uses of product, the formation of macro and micro bubbles, making the surfaces of the products perfectly uniform. ECOTEK FINISH BIO thanks to the use of special inhibitors keeps the formwork clean and protects it from corrosion.

## FIELDS OF USE

ECOTEK FINISH BIO can be used for smooth or rough formwork in steel, "plywood" or polyester, to disarm any type of concrete, with the exception of concretes with a damp earth consistency.

## SPECIFICATIONS

Aspect	liquid
Color	white
Smell	characteristic
Inflammability	non-flammable
Water solubility	soluble
Liposolubility	insoluble
Density (20°C, g/cm <sup>3</sup> )	0.95 ± 0.02
ph	9.0 ± 0.5

## MODE OF USE AND PERFORMANCE

Spray ECOTEK FINISH BIO on the formwork with appropriate airless sprayers and nozzles.

ECOTEK FINISH BIO must not be used on surfaces with temperatures above 40°C.

The product is ready to use and should not be mixed with any other product.

## EQUIPMENT

For the quick and extremely economical application of our release agents, we have prepared special equipment. Our technicians are available to evaluate the equipment and the mode of use that best suits your needs.

## PRECAUTIONS

Use according to the instructions indicated on the technical and safety data sheet.

Use full protective clothing.

Consult the toxicology sheet.

## CONSUMPTION

1 lt. for 70÷90 square meters of surface.

SHEET



TEKNA CHEM S.p.A.

Factory: Renate (MB) - Via Sirtori, z.i. 20838 - Tel. +39 0362.91.83.11

Web: [www.teknachemgroup.com](http://www.teknachemgroup.com) - E-mail: [info@teknachemgroup.com](mailto:info@teknachemgroup.com) - Fax: +39 0362.91.93.96



## PACKS

- Bulk in tanks
- 1000 lt.
- 200 lt. keg.
- 25 lt. tank

## STORAGE AND PRESERVATION

The product is frost-resistant, so it is advisable to store it at temperatures between +5°C and +40°C. ECOTEK FINISH BIO stored for more than 2 months may have a thin layer of surface oil; in this case, it is sufficient to stir the product to ensure that the surface liquid is reabsorbed. The product can be kept for 6 months in original, unopened packaging.

## LEGAL

The information contained in this technical data sheet, although representing the most advanced stage of knowledge, does not exempt the user from carrying out accurate preliminary tests in his own conditions of use and operation. Therefore, no liability is accepted for improper use of the product.

